


EXHIBIT 2

United States Patent [19][11] **Patent Number:** **5,890,172****Borman et al.**[45] **Date of Patent:** **Mar. 30, 1999**[54] **METHOD AND APPARATUS FOR
RETRIEVING DATA FROM A NETWORK
USING LOCATION IDENTIFIERS**[75] Inventors: **Gilbert Borman**, Bloomfield Hills,
Mich.; **Rajat Bhatnagar**; **Arul
Sebastian**, both of Stamford, Conn.;
Anup Mathur, Sunnyvale, Calif.;
Vinay Wadhwa, New Delhi, India;
Mukesh Kumar, Pasadena, Calif.; **C.
Vinay Kumar Singh**, Guragon, India[73] Assignee: **Tenretni Dynamics, Inc.**, Southfield,
Mich.[21] Appl. No.: **727,085**[22] Filed: **Oct. 8, 1996**[51] **Int. Cl.**⁶ **G06F 15/16**[52] **U.S. Cl.** **707/501; 707/513; 345/339**[58] **Field of Search** **707/501, 513,
707/514, 10, 102, 104; 345/329, 333, 335,
338, 339, 340, 346**[56] **References Cited****PUBLICATIONS***CNN Interactive*, "http://cnn.com/index", Feb. 20, 1998,
screen printout pp. 1-7.*AltaVista*, "http://www.altavista.com", Feb. 20, 1998, screen
printouts pp. 1-2.*Primary Examiner*—Stephen S. Hong*Attorney, Agent, or Firm*—Wilson Sonsini Goodrich &
Rosati; Paul Davis; Charles C. Cary[57] **ABSTRACT**

A computer implemented method and system for retrieving information through a browser connected to a network. A first file of information is received which includes a first mark-up language to identify contents of the information, which contents include site identifiers. The site identifiers corresponding for example to file locations on the Internet. The first file is displayed in a browser window. Responsive to receiving the first file of information by the browser, the first file of information is parsed by a jumper to generate a list of site identifiers. This list of site identifiers is then stored by the jumper and displayed in a jumper window. Responsive to an activation by the user, a computer is directed to perform the following steps. The jumper determines which of the stored site identifiers is currently selected and automatically selects the next. Next the jumper directs the browser to access the file at the site corresponding to automatically selected site identifier. Finally, the browser is directed to display the file the browser has retrieved in the browser window.

18 Claims, 14 Drawing Sheets




FIG. 1




FIG. 2





FIG. 3

U.S. Patent

Mar. 30, 1999

Sheet 4 of 14

5,890,172


(PRIOR ART)
FIG. 4

U.S. Patent

Mar. 30, 1999

Sheet 5 of 14

5,890,172



U.S. Patent

Mar. 30, 1999

Sheet 6 of 14

5,890,172




FIG. 5B

U.S. Patent

Mar. 30, 1999

Sheet 7 of 14

5,890,172





FIG. 5C


U.S. Patent

Mar. 30, 1999

Sheet 8 of 14

5,890,172





(Prior Art)
FIG. 7




FIG. 8A




FIG. 8B

U.S. Patent

Mar. 30, 1999

Sheet 12 of 14

5,890,172





FIG. 8C




U.S. Patent

Mar. 30, 1999

Sheet 14 of 14

5,890,172



5,890,172

1

METHOD AND APPARATUS FOR RETRIEVING DATA FROM A NETWORK USING LOCATION IDENTIFIERS

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

The present invention relates to information retrieval. More specifically, the invention relates to tools for traversing hypertext data.

BACKGROUND INFORMATION

The development of computerized information resources such as the Internet and various on-line services, such as CompuServe™, America On-Line™, Prodigy™ and other services has lead to a proliferation of electronically-available information. This electronic information is increasingly displacing more conventional means of information transmission, such as newspapers, magazines and even television.

The largest information resource in existence today is the Internet. The Internet is a group of client and server computers linked one to another and each having a unique identifier, DNS (distributed network server), assigned by the Internet authority in Cambridge, Mass. and Geneva, Switzerland. In order for information to be found on the Internet every file is given a specific address by which it may be located. To access the Internet a user employs what is called a browser. Currently the most popular browser is Netscape Navigator™ browser developed by Netscape Communications Corporation of Mountain View, Calif. A wide array of browsers is available for just about every platform. The browser's job is twofold. First, given a pointer to a piece of information on the net it has to be able to access the information or operate in some way based on the contents of that pointer. Second, if the document/file (hereinafter file) is encoded the browser has to translate that to a suitable format for display to the user. The display may include multimedia effects, e.g. sound and animation.

The most popular encoding of Internet files communicated between client and server is the HTML (hypertext markup language). The WWW (World Wide Web) or simply the "Web" includes all the servers adhering to this standard. Each page loaded from the Internet is a single file encoded in HTML. HTML describes the structure of a file. The structure of the file includes title, paragraphs, images and any pointers to other files.

The pointer to a specific site is called an URL (Uniform Resource Locator). The URL provides a universal, consistent method for finding and accessing information for a Web browser. The URL comprises a file type, a server I.D. (DNS), one or more directories and subdirectories, and a file name. URLs are also used as part of a hypertext link within a file to another file. These URLs then provide the browser with a way to navigate the Web. URLs contain information about a file: including file type (FTP, Gopher, HTTP), the Internet server on which the file is located (WWW.NCSA.UIUC.EDU, or FDP.APPLE.COM, or Net Com 16.Net.Com, and so on), the directory of the file, and the file name.

In order to speed the process of finding relevant information on the Internet several servers on the Internet provide an index to the Internet and a search engine. These information indexers such as Yahoo™, Excite™, Lycos™, Inktomi™, and Alta Vista™ perform two valuable functions. First, using their own Internet links, they continually search the

2

Internet and index all files on the Internet into subject categories and store this index on their own database. The information indexers also allow a client to connect to their server and enter a search query. In response the information indexer provides a list of all files on the web that meet the search criteria. Therefore, the information indexer such as Yahoo™ not only updates and maintains a topical index for all files on the web, but also makes that index searchable by a client. It should be noted that the information that is retrieved from Yahoo™ contains only a general topic identifier and the file location on the Internet for that specific topic.

It would indeed be a cumbersome process for the client seeking specific information if the indexes that were retrieved from Yahoo™ only told the searcher where to look. If this were the case, the considerable task remaining to the client would be to manually enter the network address, URL, of each file and the go through the process of retrieving that file. To overcome this problem, the search result retrieved by Yahoo™ is encoded in HTML as a hot-link which makes every "footnote" an active rather than a passive reference. These hot-links appear to the user in the browser window as bold face text which is easily distinguished from the other text based information in the file. A hot-link comprises a text description and a corresponding URL. When the user selects a hot-link the browser detects that selection and outputs the URL on the Internet to retrieve the file corresponding to that URL and display it to the user. Therefore, by merely selecting with a mouse a specific footnote in a file encoded in a markup language, a client is immediately given access to the remote web server that contains the specific file referred to in the footnote.

With a markup language such as HTML (hypertext markup language) both amateurs and professionals become authors and the footnotes on the printed page become the hypertext of the electronic page. What was a passive reference now becomes an accessible link to a related file. A markup language describes the structure of a file including headings, paragraphs, images and what are called hot-links. A hot-link displays at the user level as text or graphic and is processed for communication purposes as an URL. It is these hot-links which provide the interactive footnotes described above.

Even with the indexing provided by Yahoo™, Lycos™, Excite™, Inktomi™, Alta Vista™, etc., the process of finding the exact topic is still extremely time consuming and can involve visiting literally hundreds of Web Sites. Typically, a user will retrieve a file from an information indexer and will not only look at the files retrieved by selecting the indexer's hot-links, but will also select other hot-links in the retrieved documents. This process of starting a search that begins with an initial hot-link and following a search trail that leads to successive files each increasingly displaced from the starting point is known as a drill-down. The problem with current browsers is that when a user has drilled-down through many levels of sites, the only way to return to the original HTML file is to hit the browser's back key which moves the user up one level at a time through the original search tree back to level "1." Only then can the user access other hot-links retrieved in the original search.

What is needed is a more efficient way to conduct a search.

SUMMARY

A first object of the invention is to provide operational controls for simplified Internet navigation from various sites and back again.

5,890,172

3

A second object of the invention is to save users time and effort in finding information on the Internet.

A third object of the invention is to enable the publication of a new format for on-line magazines, called Netazines, which allow publishers to leverage the navigational controls provided in the invention product to foster a new paradigm for browsing magazine style information on the Internet.

A computer implemented method and system for retrieving information from a network. In a first embodiment a first file of information is received which may include a first mark-up language to identify contents of the information, which contents include site identifiers. The site identifiers corresponding for example to file locations on the Internet. The first file is displayed in a browser window. Responsive to receiving the first file of information by the browser, the first file of information is parsed by a jumper to generate a list of site identifiers. This list of site identifiers is then stored by the jumper and displayed in a jumper window. Responsive to an activation by the user, a computer is directed to determine which of the stored site identifiers is currently selected and automatically selects an other. The other includes the first, the prior, the next, or the last on the list.

In a second preferred embodiment a first file of information in a hypertext markup language is received and displayed in the browser window. The first file of information also contains site identifiers and other information. The first file is displayed in the browser and is parsed, and the site identifiers from that file are stored by the jumper in a list. The stored list of site identifiers is displayed in the jumper window. Responsive to a selection by a user of automatic mode, a computer is directed to perform the following steps. The jumper selects a first site identifier from the stored list of site identifiers. The jumper directs the browser to access the file at the site corresponding to the automatically selected site identifier. The browser, is directed by the jumper, to display the file in the browser window. Then the jumper initiates a delay of a predetermined interval. At the end of the interval the jumper selects the next site identifier from the stored list of site identifiers. The jumper directs the browser to access the file at the site corresponding to the automatically selected next site identifier. The browser, is then directed by the jumper, to display that file in the browser window. The jumper continues to repeat this animation loop from one site identifier in the stored list of site identifiers to the next, until either the entire list of site identifiers has been sent to the browser and displayed, or until the user terminates the process. In this manner, an animated tour of all files having site identifiers parsed from the first file is displayed in the browser window under the direction of the jumper.

In a third embodiment, a first file of information in a hypertext markup language is received and displayed in a browser window. The first file of information also contains a site identifier and other information. The first file of information is displayed by the browser in the browser window. Responsive to receiving the first file of information, the jumper parses the first file and extracts and stores a list comprised of first file site identifiers. The stored list of site identifiers is then displayed in the jumper window. The user is allowed to select from the browser window a specific site identifier, known as a search level "1" site identifier, and responsive thereto to cause the browser to access and display a second file retrieved from the site corresponding to the selected level "1" site identifier. This second file includes a hypertext markup language and site identifiers. The user is again allowed to select from the browser window a specific site identifier and responsive thereto causes the browser to

4

access and display a third file retrieved from the site corresponding to the selected site identifier. This process can be repeated in the browser, until the user has completed their search, or drill-down.

Responsive to the completion of the drill-down in the browser, as indicated to the jumper by receipt of a single jump selection from the user, the computer is directed to perform the following steps. The jumper determines which of the stored level "1" site identifiers is currently selected and automatically selects the single jump level "1" site identifier. Next the jumper directs the browser to access the file at the site corresponding to the single jump selected level "1" site identifier. Finally, the browser is directed to display the file the browser has retrieved in the browser window. This allows the user to return to the files pointed to by the original level "1" site identifiers without having to traverse in reverse serial order the site identifiers selected in the drill-down.

BRIEF DESCRIPTIONS OF DRAWINGS

The present invention is illustrated by way of example and not limitation in the figures in which like references indicate like elements and in which:

FIG. 1 shows a client server system including embodiments of the jumper invention.

FIG. 2. shows a more detailed view of the client server system illustrated in FIG. 1.

FIG. 3. shows a preferred embodiment of the screen interface and tool bar of the jumper.

FIG. 4 shows a prior art browser user interface, and the query form of an information index provider.

FIGS. 5A-C shows a the initial stages of a search session utilizing a prior art browser and the jumper.

FIG. 6. shows a later stage in the search session of FIGS. 5A-C.

FIG. 7. shows the steps in the search process in prior art browsers.

FIGS. 8A-C shows the processes of a search session on the jumper.

FIGS. 9A-B show the search traversal patterns of a prior art browser and the jumper.

DETAILED DESCRIPTION

One embodiment of the invention is a method and apparatus for retrieving information through a browser connected to a network, and providing the information to a user. Although the following will be described with reference to certain particular embodiments, including data structures, flow of steps, hardware configurations, menu configurations, etc . . . , implementation of the invention can be practiced without these specific details.

One embodiment of the invention allows a search to be conducted in non-linear order. This may be done in either single jump or automatic jump mode utilizing a jumper. A search tree does not therefore need to be traversed in reverse serial order after a drill-down as is required utilizing prior art browsers. The invention allows a searcher to jump across multiple levels at a time.

Search Levels:

The operation of prior art browsers is best described by reference to FIG. 9A. FIG. 9A shows a series of hypertext files. The files may be resident on a hard drive, a local network, a wide area network or the Internet. Three hot-links are shown 920, 922, 924 on file 902. Hot-link 924 is shown

5,890,172

5

as linked to four levels of files. Selecting hot-link **924** causes the browser to access file **926**, which is a level 2 file. Selecting the first hot-link on file **926** causes the browser to access file **928**, which is a level 3 file. Selecting the first hot-link on file **928** causes the browser to access file **930**, which is a level 4 file. Finally, selecting the first hot-link on file **930** causes the browser to access file **932**, which is a level 5 file. Selecting hot-link **922** causes the browser to access file **934**, which is a level 2 file. Selecting hot-link **920** causes the browser to access file **936**, which is a level 2 file.

The traversal steps from hot-link **924** through **926**, **928**, **930** and **932** constitute a drill-down from level 1 to level 5. Prior art browsers require that the user, in order to return to the original file **902**, must traverse the search tree in reverse serial order. As shown serial return **904** traverses from **932** to **930**, serial return **906** traverses from **930** to **928**, serial return **908** traverses from **928** to **926**, and finally serial return **910** traverses from **926** to **902**, the initial starting point. This requires the needless steps of visiting each of the branches traversed in the drill-down. This process is unnecessarily time consuming when compared with the capabilities of the current jumper invention.

FIG. 9B shows the same tree structures as does FIG. 9A. FIG. 9B shows the use of one embodiment of the invention to traverse many levels at a time in either single jump or automatic jump mode. In the single jump mode when the searcher has reached level 5 file **932**. If the user wants to return to level 1 they do not need to do so in reverse serial order, as is required by prior art browsers. Instead, the user directs the jumper to access the next level 1 hot-link. In response, the jumper returns the user in a single jump **914** from level 5 file **932** to the level 2 files pointed to by the hot-links in the level 1 file **902**. Much time is saved and the user can proceed to search other level 1 hot-links. In automatic jump mode, the user instructs the jumper to access all hot-links on the level 1 file **902**. In response, the jumper directs the browser to access and display in the browser window each of level 2 files **926**, **934** and **936**. These files are accessed by the browser in response to the jumper sending at timed intervals each of hot-links **924**, **922**, and **920** from a parsed hot-link list to the browser. The browser accesses each of the files **926**, **934**, and **936** to which hot-links **924**, **922**, and **920** respectively point. This allows the user to see an animation in the browser window for a timed interval.

Hardware:

In order to better understand the operation of a jumper, it is necessary to first understand an environment in which the jumper is practiced. FIGS. 1-2, show the hardware environment in which the jumper operates. As shown in FIG. 1, an Internet **22** is connected to client **20** by an incoming Internet line **24** and an outgoing Internet line **26**. Jumper **28** and browser **30** are part of client **20**. Internet **22** comprises servers **32**, **34**, **36**, and **38**. Each server contains HTML files. The client and all servers are linked electronically. Server **34** is shown as the server of an information indexer. The server comprises a CGI **42** (common gateway interface), forms **44** on which a user query is entered, and storage containing an updated topical index **46** of all files on the web. To access a specific site on the network, browser **30** outputs an URL across outgoing Internet line **26**. Routers on the Internet establish an electronic link between the client **20** and the appropriate server **32-38**. Communications with the Internet are received on incoming Internet line **24**.

The client hardware architecture for both the browser and the jumper is shown in greater detail in FIG. 2. The client **20** contains storage **204**, computational hardware **202**, operat-

6

ing system **206**, and GUI (Graphical User Interface) **200**. The storage **204** contains a storage segment **230** in which the jumper stores parsed HTML files. Hardware **202** comprises a microprocessor, an I/O interface, a display and a bus connection to storage **204**. The operating system **206** may comprise a bios and an operating environment such as System **7™**, Unix™ or Windows™. The GUI **200** comprises jumper **28** and browser **30**. Browser **30** comprises user I/O **208** and presenter **210**. The jumper **28** comprises user I/O **212**, presenter **214**, and parser **216**.

The operation of hardware **202** is controlled by the operating system **206**. The operating system and graphical user interface (GUI) **200**, create the local environment in which the jumper **28** and browser **30** exist. The browser user I/O **208** handles the tasks of sending and retrieving communications **218** via the operating system **206** and hardware **202** to the Internet **22**. The browser handles Internet communications for the jumper. The browser user I/O communicates with the jumper user I/O **212** via jumper-parser I/O protocol **224**. The browser user I/O also handles the task of translating files received from the Internet, e.g., HTML encoded files, to the presenter **210** via presenter protocol **220**. Additionally, browser user I/O uploads at the direction of jumper user I/O **212**, HTML encoded files to parser **216** via browser I/O-jumper parser protocol **222**.

Jumper parser **216** handles the task of converting an HTML encoded file uploaded from browser user I/O **208** into a format suitable for a single jump or automatic jump mode search, as discussed above in connection with FIG. 9B. The parser extracts from the HTML file: an advertisement, a plurality of URLs and topic descriptors corresponding to each URL. The parser passes these via jumper-parser I/O protocol **226** to jumper user I/O **212**. Jumper user I/O **212** communicates with jumper presenter **214** via jumper I/O-presenter protocol **228** to display to the user available jump sites and to provide a user interface by which the user may input commands. Jumper user I/O also communicates with browser I/O **208** via browser I/O-jumper I/O protocol **224**.

User interface:

An embodiment of the jumper user interface is shown in FIG. 3. This interface allows the user to see all the hot-links on a given level and to select a hot link in either single jump or automatic jump mode as described above in connection with FIG. 9B. The jumper thus enhances the search capabilities of the browser.

Jumper window **300** comprises a menu bar **302**, a button bar **304**, an advertisement area **306**, a jump site window **308**, and a drop-down list button **310**. The jumper menu bar contains file, edit, action, and help items. Jumper button bar contains a first entry button **312**, a previous entry button **314**, a random jump button **316**, a next entry button **318**, a last entry button **320**, a start timer button **322**, a stop timer button **324** and a refresh/update button **326**.

The jump site window **308** has an associated drop down list accessible by selecting drop-down list button **310**. This list comprises parsed hot-links. These hot-links are extracted from a file initially retrieved by the browser. Any one of the hot-links in the parsed list can be selected by the user with a mouse. This drop-down list provides one method for selecting a specific Internet site to jump to. Advertisement area **306** contains an advertisement parsed from an HTML page received by the browser. Button bar **304** provides controls for single jump and automatic jump mode. All buttons relate to the hot-links in the jumpers parsed list regardless of how far the user has drilled-down in the browser. All buttons return the user to at least one of the

5,890,172

7

hot-links on the list and direct the browser **30** shown in FIGS. 1–2 to retrieve a file from the site corresponding to the URL associated with the hot-link and further direct the browser to display that file to the user.

First entry button **312** allows the user to return from a drill-down to the first entry on parsed list. Previous entry button **314** returns the user to the prior hot-link on the list. Random jump button **316** returns the user to a randomly selected hot-link on the parsed list. Next entry button **318** selects the next hot-link on the list, and last entry button **320** accesses the last entry on the list. Start timer button **322** initiates the automatic and successive selection of every hot-link on the parsed list and the browser responsive thereto, displays for the user a file retrieved from the URL corresponding to each hot-link. The animation initiated by start timer button is terminated by stop timer button **324**. Refresh/update button **326** causes all hot-links in a file which the browser has retrieved to be parsed and uploaded and displayed in the drop-down list of jumper window **300**. Additionally, this parsed list is stored in HTML storage segment **230** as shown in FIG. 2.

In alternate embodiments the jumper window may take any of several forms. The user interface may include popup or persistent window, a toolbar, a menu modification of the browser window, a toolbar modification of the browser window, or the use of accelerator keys on the keyboard.

FIG. 4 shows a prior art browser user interface and a query form of an information index provider. This interface allows the user to access web files and also displays the file contents to the user. The browser interface **400** is that of Netscape Navigator™. The browser interface includes a browser menu bar **402**, a site window **404**, and a window **406** for viewing a file. The browser menu bar includes a back button **412** and a home button **414**. The file shown in the view window is the query form **408** of Yahoo™. The query form has a query field **410**.

The browser menu bar **402** generally provides for editing and saving files. Back button **412** allows the user to move back a search tree in reverse serial order as shown in FIG. 9A. Home button **414** allows the user to return to their home page **900** in the browser window. The browser site window **404** displays the URL corresponding to the file currently being displayed, in this case the query form **408** of Yahoo™. The query form is encoded in a markup language and contains a query field **410** in which the user may enter the search topic for which a topical of the web is desired. In this case, the search topic is “Rat.” When the search topic is entered, it is sent by the browser over the web to Server **34** owned by Yahoo™ **40** and shown in FIG. 1. Conducting a search:

FIGS. 5A–C show the initial stages of a search session conducted with the jumper and browser. A browser interface **400**, a file retrieved by the browser, and a jumper window **300** are shown. These are the basic tools for the demonstrative search. The initial file retrieved from Yahoo™ in response to the query “Rat” is shown as an upper page portion **502a** and a lower page portion **502b** in FIGS. 5A–B and 5C, respectively. These are accessed by scrollable window bar **500**. The retrieved file contains an advertisement **504**, a search result summary **506**, a plurality of hot-links of which **508–514** and **580–584** are referenced. A representative hot-link **514**, is shown to contain both an URL **516** and a text portion **518**. In FIG. 5C a jumper drop down list **586** is shown. In addition, the retrieved file also contains a next feature **588**.

In response to the entry of the query “Rat” as shown on FIG. 4, the query is sent by browser to Yahoo™. The topical

8

index **46** at Yahoo™, shown in FIG. 1, is searched and the file **502a–b** containing all related level 1 hot-links and other information is returned to the client **20** and displayed to the user by the browser as **502a–b**. Page **502a** is captioned with an advertisement **504**. Immediately below the advertisement is a search result summary **506**, which indicates 74 matches pertaining to the word “Rat” and display of the first 20 hot links for those matches. Various hot-links with subject descriptions appear on the page in bold text with underlining. These are, for example, **508**, “Entertainment, Humor . . .”, **510**, “Regional Alternative Theater . . .”, **512**, “Space RAT . . .”, **514**, “Agrizap, Inc . . .”.

Each hot-link as discussed above is an active reference. For example the hot-link **514** comprises a hypertext identifier “<A”, an URL **516**, a text portion **518** and a closing identifier. The browser displays to the user only text portion **518** and any images that may accompany it. These are highlighted and underlined on the user display to indicate to the user that when they are selected with a mouse a corresponding URL will be sent by the browser to the Internet to access the specific file referred to by the URL.

As shown in FIG. 5B, jumper window **300** has been refreshed via refresh/update button **326**, discussed above in connection with FIG. 3. Responsive to selection of refresh/update button **326**, the file **502a–b** is passed from the browser **30** to the jumper parser **216** as shown in FIG. 2. All hot-links including the referenced hot-links **508–514** and **580–584** are extracted and passed to jumper user I/O **212**. These are passed to jumper presenter **214** and displayed in the jumper window **300**. Specifically the advertisement **504** is displayed in jumper advertisement area **306**, and all hot-links **508–514** and **580–584** are put in the jumper drop down list. The first of these hot-links **508** is displayed in the jumper site window **308**.

In FIG. 5C, the lower portion **502b** of the retrieved HTML page is shown. It contains hot-links **580, 582, 584**. In jumper window **300** and specifically jumper site window **308** thereof, the jumper drop-down window, **586**, is shown. This window has been accessed by the user’s selection of jumper drop-down list button **310**. The drop-down list contains all hot-links that were obtained from the original file **502a–b** including the referenced hot-links **508–514** and **580–584**.

Now, by reference to FIG. 6, a later stage of the search session is shown. FIG. 6 shows a file **600** in browser window **406**, an URL corresponding to file **600** in browser site window **404**, and a highlight **602** around hot-link **580** in both the jumper drop-down list window **586** and the jumper site window **308**. The file **600** was obtained in a drill-down conducted in the browser window **406**. The steps in that drill-down intervening between FIG. 5C and FIG. 6 have not been shown. The drill-down however resembles that shown and discussed above in connection with FIG. 9A. The file **600**, shown in browser window **406** is four levels removed from the initial level 1 hot-link **580**. The drill-down was conducted on the browser view screen by selecting the hot-links presented in the files retrieved by the browser. If the user desires to return to the an other hot-link from the level 1 file, shown as **502a–b** in FIGS. 5A–C, from this file **600**, they could use the browser menu bar to do so but it would be slow. They would have to select back button **412** four times to return them one level at a time in reverse serial order through their entire search back to the level 1 file. The process is time consuming. Alternately, if they selected the browser home key **414** they would return to their home page and lose the level 1 search results. Neither of these alternatives is acceptable. Both of these alternatives are cumbersome.

5,890,172

9

If the jumper product is utilized instead, the user has several options. As a first option, the user may select one of jumper buttons **312, 314, 316, 318** or **320** to return to respectively: a first, a previous, a random, a next, or a last of the hot-links shown in FIG. 6 in jumper drop-down list window **586**. In response to user selection, the file corresponding to the selected hot-link will be retrieved and displayed in the browser window **406**. As a second option, the user may select start timer button **322** to initiate the automatic and successive selection at a timed interval of every hot-link on the parsed list. In response to the automatic jump mode selection, each file corresponding to the selected hot-link will be retrieved and displayed by the browser for the timed interval. As a third option, the user may select drop-down window button **310** and select a given entry from the drop down list by clicking on it with a mouse. In response to their selection the file corresponding to the selected hot-link will be retrieved and displayed in the browser window **406**. Alternately, another instance of browser can be opened to display the selected file. All of these choices enhance the search, and none require multiple reverse serial order steps to return to the level 1 hot-links. Process Flow:

FIG. 7 shows the process connected with conducting a search utilizing a prior art browser. Commencing with start process **700**, a connection process **702** results in Yahoo's™ home page **408** and query form being displayed in browser window **406**, as shown in FIG. 4. Then in query process **704**, the user enters a search topic, e.g., "Rat", in information indexer query field **410**. In response to the entry of that search topic, the browser sends the query to server **34** of the search index provider, e.g., Yahoo™, the relevant topical identifiers and URLs are uploaded on an HTML encoded file/page and presented to the user in page receipt process **706**. Subsequently, when a user utilizing a mouse selects one of the hot-links shown on that page, e.g., **502a-b**, then that selection is detected in site access decision **708**. The URL corresponding to the last selected hot-link is output over the Internet to access the file indicated by that URL and that file is uploaded and displayed in access process **710** to the user. Subsequently, in history creation process **712**, that URL is added to a stack comprising in LIFO order the most recently accessed files, including the complete URL for those files. Control is then returned to back-one decision **714** which decision is also reached if a negative determination is made in site access decision **708**. In back-one decision **714**, a determination is made as to whether the user has selected back button **412** on the browser menu **402**. If that selection has been made, then control is passed to repeat history process **716** in which the previous site visited is popped from the history stack and in access process **718** the browser accesses the site and file indicated by the prior URL and presents that in its view window to the user. Control is subsequently returned to site access decision **708**.

Alternately, if in back-one decision **714** a negative determination is reached the browser awaits the next user command **720**.

In FIGS. 8A-C the process connected with one embodiment of the current invention is shown. It contrasts with the prior art process, in that the user may return to the level of files pointed to by any level one hot-link immediately. The cumbersome process and many steps of reverse serial order traversal discussed above in FIG. 7, are not therefore necessary. FIG. 8A is an overall view of the process connected with either the single jump or automatic jump mode. FIG. 8B details the specific steps connected with the automatic jump mode. FIG. 8C details the specific steps connected with the single jump mode.

10

Commencing with FIG. 8A and start jumper process **800** control is passed to refresh decision **802**. In the event, a determination is made that refresh/update button **326** shown in FIG. 3 has been selected, then control is passed to fetch and parse process **804** in which an HTML encoded page displayed in the browser view window is uploaded and parsed into an advertisement and hot-links. These are displayed in the jumper advertisement area **306** and the jumper drop-down window **586**, respectively. Then in history decision **806**, the determination is made as to whether the jumper history maintain option has been selected. This option is found under the edit portion of the menu bar **302**. In the event that this option has been selected, then control is passed to append and store process **808** in which the hot-links extracted in fetch and parse process **804** are appended and stored with previous hot-links in the parsed HTML files in storage segment **230** shown on FIG. 2. Control is then passed to display URL process **812**. Alternately, if a negative determination is made in history decision **806**, then control is passed to store process **810** in which the hot-links from the fetch and parse process **804** replace any existing stored hot-links. Subsequent control also is passed to display URL process **812**. In display URL process **812**, the hot-links are displayed in the jumper drop-down window **586** as shown in FIG. 6. Control subsequently passes to display advertisement process **814** in which an image corresponding to an advertisement parsed from the browser page is placed in the jumper advertisement area **306**.

As discussed above in connection with refresh decision **802**, if a negative determination is made that the refresh button has not been pressed, then control passes also to display advertisement process **814** in which the advertisement from the page currently displayed on browser window **406** is uploaded and displayed in the jumper advertisement area **306**. Control subsequently passes to start timer decision **816**. If the user has selected start timer button **322** from the jumper menu bar, then automatic jump mode commences in a manner set forth in FIG. 8B. Alternately, if a negative determination is reached, then control is passed to jumper button select decision **818**. A determination is made as to whether the user has selected any one of buttons **310-320** in the jumper window **300**. In this event, control is passed to processes set forth on FIG. 8C and corresponding to single jump mode. The return from either the automatic jump or single jump process is via splice block B to jumper button select decision **818**. Finally, when a negative determination is reached in jumper button select decision, control returns to refresh decision **802**. This completes the overall processing connected with the jumpers tree traversal.

In FIG. 8B, the automatic jump mode of the search process is shown in greater detail. This process allows a user to view an animated tour of the level 2 files pointed to by the level 1 hot links in the browser window. Commencing with splice block A, control passes to memory fetch process **840** in which the first URL, of the hot-links in storage segment **230** shown in FIG. 2, is fetched by the jumper. In the next process, jumper-browser process **842** the first URL is sent to the browser, user I/O **208** caused the browser to access the specific site and file on the site, to upload the file and to display the file in the browser window **406**. In one embodiment, if the browser is still loading a previous file when the jumper-browser process **842** is reached, then sending the browser the URL interrupts the loading of the previous file. In another embodiment, the jumper-browser process **842** does not interrupt the loading of the previous file. In a third embodiment, whether the jumper-browser

5,890,172

11

process **842** interrupts the loading of the previous file is a user configurable option.

Control is then passed to delay process **844** in which a user selectable display interval causes the page image to be displayed on browser window **406** for the selected time interval. At the end of that time interval, control is passed to memory fetch process **846** in which the next URL in the parsed HTML file is uploaded and in last of list decision **848** a determination is made as to whether that URL is the last among the stored URLs. In the event that determination is in the negative, control returns to jumper-browser process **842** for the timed display of the next accessed URL. This loop from jumper-browser process **842** through last of list decision **848** constitutes a user configurable animation, in which a set of URLs which have been parsed and stored are now used to drive an automatic retrieval and display process.

Alternately, in last URL decision **848**, if a determination is made in the affirmative, control is passed to "next" link decision, **850**. In next link decision **850** a determination is made as to whether the last URL also includes a query for the next **10** entries corresponding to the example shown in FIG. **5C** and indicated by **588**. In the event that determination is in the affirmative, control is passed to jumper-browser-jumper process **852**. In process **852** the query for the next **10** hot-links is sent to Yahoo™. In response the next HTML encoded page containing the **10** hot-links is retrieved. Control is passed to parse process **854** in which all the URLs and corresponding text identifiers are parsed along with the image corresponding to the advertisement. Then in buffer process **856**, the parser output is stored for this session. Control then passes to memory fetch process **840** for automatic retrieval and display. Alternately, if in "next" link decision **850**, a negative determination is made, then in jumper-browser process **858**, the last URL is sent to the browser to both access and display the file corresponding to the last URL. Subsequently, control is passed to splice block **B** for a return to hot-link select decision **818**.

The process corresponding to the single jump mode is shown in FIG. **8C**. This process allows the user to select a specific level **1** hot-link and have the browser retrieve and display the level **2** file corresponding to the selected level **1** hot-link. In window process **880**, the jumper drop-down window **586** is automatically opened, as is shown in FIG. **5C**. Then in drop-down button process **882** a determination is made as to whether the button selected by the user and detected in jumper button select decision **818**, was the drop-down list button **310**. If the user did select button **310** then the user has not yet selected a specific hot-link from the parsed hot-links in the jumper drop-down window **586**. Control is then passed to wait process **884**. When the user selects a specific entry from the drop-down list control passes to locate select process **886**. Alternately, if a negative determination is reached in jumper button select decision **818** then control is passed directly to locate select process **886**. A negative determination in jumper select decision **818** means that one of jumper buttons **312**, **314**, **316**, **318** or **320**, was selected thereby indicating a specific user choice for the single jump location. These buttons were discussed above in connection with FIG. **3**.

In locate select process **886** a determination is made as to which of the hot-links in the jumper drop-down window was selected. If, for example, first entry button **312** were selected then the first of the hot-links in the list is selected. Alternately, if the user selected drop-down window button **310** and then mouse selected an entry e.g. the fourth entry on the drop-down list, then that entry would be highlighted. In the example shown in FIG. **6** the user has selected hot-link

12

580 and that selection, the "Ricky Rock Rat" hot-link is detected by the jumper.

Subsequent to selection detection, control is passed to jumper-browser process **888**. The URL corresponding to the selected hot-link is passed by the jumper to the browser causing the browser to locate and subsequently display a file corresponding to that URL. The jumper continues to display all level "1" sites as hot-links. In the next step highlight process **890** the selected hot-link is highlighted, as shown for example in FIG. **6** as highlight **602** around selected hot-link **580**, "Ricky Rock Rat". After the highlight process, the selected hot-link on the drop-down list is copied to the jumper site window **308** in copy process **892**. Subsequently, in process **894** the jumper drop-down window is closed.

When the browser displays the above mentioned file, the user may conduct a drill-down on the hot-links in that file in the browser window. In that case, the browser window is active and the jumper window is inactive. When the drill-down is complete and the user reactivates the jumper window by mouse clicking on it, that reactivation is detected in process **898** and control is passed to jumper select decision **818** via the splice block **B**, shown in FIG. **8A**.

The following describes additional embodiments of the invention. Except where stated in alternative form, each of these embodiments include features that can be combined with the features discussed above.

Some alternative embodiments provide better integration of the jumper's functions and the browsers functions. In one embodiment of the invention, when a user initiates a search in the browser, the jumper automatically starts and begins parsing the results of the search. This saves the user from having to start the jumper separately from the browser. In another embodiment, the jumper functions are built directly into the browser. In a different embodiment, the jumper is implemented as an application, such as an applet, which is sent to the browser by the search engine. All of these embodiments provide a more integrated jumper/browser environment for the user.

Some alternative embodiments provide the user with more powerful tools for traversing the search results. In one embodiment, the categories in the search results are specially tagged (e.g., with a previously unused HTML tag) to indicate category fields as opposed to simple URLs. Alternatively, the categories can be parsed given their location in the search result (e.g., not indented). In an embodiment that includes category identification, the jumper includes functions for jumping from one category to the next category, in addition to being able to jump from one site identifier to the site identifier. As an enhancement to this embodiment, the user is presented with additional buttons for jumping from category to category. In another embodiment, the user can define how many site identifiers should be parsed from the search results. For example, if the search results provide twenty site identifiers, but the user may only want the first five identifiers, the user can specify that only the first five identifiers be provided. Similarly, in another embodiment, the user can specify what types of results should be parsed (e.g., only categories). Alternatively, in another embodiment, the jumper parses all the site identifiers, but the user specifies how many or what type to display.

In another embodiment, the user will be able to invoke the product from within their electronic e-mail box simply by double-clicking on attached files. These files may be encoded in markup language. In another embodiment, the HTML parsed files for both transmission and receipt by users would be able to be compressed and decompressed by

5,890,172

13

users with simple click commands common to normal software operations. In another embodiment, the product will not require an additional instance of the presenter to be invoked upon return to the original home page. In still another embodiment of the product, the list box will contain a drag and drop user interface which will allow the user to cut and paste URLs from one list to another and compile their own individual lists to their preferred selection and taste. In still one more embodiment of the product, the user will be able to adjust and modify the overall interface of various URLs, hot-links and other files viewable within the presenter to both highlight the various objects mentioned previously for marking the users place in the list that they are working from, and similarly be able to change the nature of the highlight of such previously mentioned item to be noted as important by a permanent highlighting of the particular object.

Thus, a method and apparatus for retrieving information has been described. Note that though the foregoing has particular utility and has been described with reference to certain specific embodiments in the figures and the text, that one may practice the present invention without implementing all of these specific details. Thus, the figures and the text are to be viewed in an illustrative sense only, and not limit the present invention. The present invention is only to be limited by the appended claims which follow.

DEFINITIONS

1. NETWORK: A network is a hard drive, a local network, a wide area network, an intranet, the internet or any series or combination of computers or computing hardware.
2. FILE: A file is a collection of data that may be coded or unencoded. Coded files may contain the HTML, SGML or other mark up language. Unencoded files comprise; audio, visual, graphics, and/or video. Files may be encrypted or unencrypted during transmission. An electronic mail message is also considered to be a file. In addition, attachments to electronic mail are also considered files.
3. PRESENTER: A presenter is an interactive information media either visual or audio, animated or static, graphical or textual, audio or silent.
4. SITE IDENTIFIER: A site identifier is a pointer to a file. What is claimed is:
 1. A computer implemented method for searching on a local computer a network of nodes with data files stored at corresponding ones of the nodes and each of the data files identifiable by a location identifier and several of the data files containing location identifiers for others of the data files, and the method for searching comprising the acts performed on the local computer of:
 - constructing a search window on a display screen of the local computer;
 - displaying a first and a second icon separate from the search window on said display screen;
 - retrieving an initial data file from the network together with displaying the initial data file in the search window, and the initial data file including location identifiers;
 - parsing the location identifiers from the initial data file to form an initial list of location identifiers together with storing the initial list, responsive to a selection of the first icon; and
 - retrieving a first data file corresponding to a selected one of the location identifiers in the stored initial list together with displaying the first data file in the search window, responsive to a selection of the second icon.

14

2. The computer implemented method of claim 1 wherein; said initial data file comprises information in a markup language; and
- said location identifiers comprise URLs.
3. The computer implemented method of claim 1 wherein; said initial file and said first data file comprise information in a markup language; and
- said location identifiers comprise URLs.
4. The computer implemented method of claim 1 wherein said retrieving act further comprises;
 - retrieving the first data file corresponding to the one of the location identifiers in the stored initial list selected from a group consisting of: a next location identifier, a prior location identifier, a first location identifier and a last location identifier, together with displaying the first data file in the search window, responsive to a selection of the second icon.
5. A computer usable medium having computer readable program code means embodied therein for searching on a local computer a network of nodes with data files stored at corresponding ones of the nodes and each of the data files identifiable by a location identifier and several of the data files containing location identifiers for others of the data files, the computer readable program code means in said article of manufacture comprising:
 - computer readable program code means for causing a computer to construct a search window on a display screen of the local computer;
 - computer readable program code means for causing a computer to display a first and a second icon separate from the search window on said display screen;
 - computer readable program code means for causing a computer to retrieve an initial data file from the network and displaying the initial data file in the search window, and the initial data file including location identifiers;
 - computer readable program code means for causing a computer to parse the location identifiers from the initial data file to form an initial list of location identifiers together with storing the initial list, responsive to a selection of the first icon; and
 - computer readable program code means for causing a computer to retrieve a first data file corresponding to a selected one of the location identifiers in the stored initial list together with displaying the first data file in the search window, responsive to a selection of the second icon.
6. The computer readable program code means in said article of manufacture of claim 5 comprising:
 - computer readable program code means for causing a computer to retrieve the initial data file, wherein said initial data file, comprises information in a markup language and said location identifiers comprise URLs.
7. The computer readable program code means in said article of manufacture of claim 5 comprising:
 - computer readable program code means for causing a computer to retrieve the initial data file and the first data file, wherein each of said initial and said first data files, comprise information in a markup language and said location identifiers comprise URLs.
8. The computer readable program code means in said article of manufacture of claim 5 comprising:
 - computer readable program code means for causing a computer to retrieve the first data file corresponding to the one of the location identifiers in the stored initial list

5,890,172

15

selected from a group consisting of: a next location identifier, a prior location identifier, a first location identifier and a last location identifier together with displaying the first data file in the search window, responsive to a selection of the second icon.

9. A computer implemented method for searching on a local computer a network of nodes with data files stored at corresponding ones of the nodes and each of the data files identifiable by a location identifier and several of the data files containing location identifiers for others of the data files, and the method for searching, comprising the acts performed on the local computer of:

constructing a search window on a display screen of the local computer;

displaying a first and a second icon separate from the search window on said display screen;

retrieving an initial data file from the network together with displaying the initial data file in the search window, and the initial data file including location identifiers;

parsing the location identifiers from the initial data file to form an initial list of location identifiers together with storing the initial list, responsive to a selection of the first icon; and

automatically retrieving at a predefined time interval data files corresponding to each of the location identifiers in the stored initial list, together with successively displaying the data files in the search window, responsive to a single selection of the second icon.

10. The computer implemented method of claim 9 wherein:

said initial data file comprises information in a markup language; and

said location identifiers comprise URLs.

11. The computer implemented method of claim 9 wherein:

said initial data file and said first data file comprise information in a markup language; and

said location identifiers comprise URLs.

12. A computer usable medium having computer readable program code means embodied therein for for searching on a local computer a network of nodes with data files stored at corresponding ones of the nodes and each of the data files identifiable by a location identifier and several of the data files containing location identifiers for others of the data files, and the computer readable program code means in said article of manufacture comprising:

computer readable program code means for causing a computer to construct a search window on a display screen of the local computer;

computer readable program code means for causing a computer to display a first and a second icon separate from the search window on said display screen;

computer readable program code means for causing a computer to retrieve an initial data file from the network together with displaying the initial data file in the search window, and the initial data file including location identifiers;

computer readable program code means for causing a computer to parse said initial data file to form an initial list of location identifiers together with storing the initial list, responsive to a selection of the first icon;

computer readable program code means for causing a computer to automatically retrieve at a predefined time interval data files corresponding to each of the location

16

identifiers in the stored initial list, together with successively displaying the data files in the search window, responsive to a single selection of the second icon.

13. The computer readable program code means in said article of manufacture of claim 12 comprising:

computer readable program code means for causing a computer to receive said initial data file, wherein said initial data file, comprises information in a markup language and said location identifiers comprise URLs.

14. The computer readable program code means in said article of manufacture of claim 12 comprising:

computer readable program code means for causing a computer to receive said initial data file and said first data file, wherein said initial data file and said first data file, comprise information in a markup language and said location identifiers comprise URLs.

15. A computer-implemented method for searching on a local computer a network of nodes with data files stored at corresponding ones of the nodes and each of the data files identifiable by a location identifier and several of the data files containing location identifiers for others of the data files, and the method for searching comprising the acts performed on the local computer of:

constructing a browser window on a display screen of the local computer;

displaying a first icon and a list window separate from the browser window on said display screen;

retrieving into the browser window an initial data file from the network together with displaying the initial data file in the browser window, and the initial data file including location identifiers;

parsing the location identifiers from the initial data file to form an initial list of location identifiers together with storing and displaying the initial list in the list window, responsive to a selection of the first icon; and

retrieving a first data file corresponding to a one of the location identifiers displayed in the list window together with displaying the first data file in the browser window, responsive to a selection of the corresponding one of the location identifiers displayed in the list window.

16. A computer-implemented method of of claim 15, wherein:

wherein said initial data file and said first data file comprise information in a markup language and said location identifiers comprise URLs.

17. A computer usable medium having computer readable program code means embodied therein for for searching on a local computer a network of nodes with data files stored at corresponding ones of the nodes and each of the data files identifiable by a location identifier and several of the data files containing location identifiers for others of the data files, the computer readable program code means in said article of manufacture comprising:

computer readable program code means for constructing a browser window on a display screen of the local computer; computer readable program code means for displaying a first icon and a list window separate from the browser window on said display screen;

computer readable program code means for retrieving into the browser window an initial data file from the network together with displaying the initial data file in the browser window, and the initial data file including location identifiers;

computer readable program code means for parsing the location identifiers from the initial data file to form an

5,890,172

17

initial list of location identifiers together with storing and displaying the initial list in the list window, responsive to a selection of the first icon; and
computer readable program code means for retrieving a first data file corresponding to a one of the location identifiers displayed in the list window together with displaying the first data file in the browser window, responsive to a selection of the corresponding one of the location identifiers displayed in the list window. 5

18

18. The computer readable program code means in said article of manufacture of claim **17** comprising:
computer readable program code means to retrieve said initial data file of information, wherein said initial data file, comprises information in a markup language and said location identifiers comprise URLs.

* * * * *